## WE CLAIM:

	WE CLAIM.
Sab.	$\Delta D$
1	1. A hand-held display system for playing video games, comprising:
2	a housing grippable by a user's hands;
3	a liquid crystal display viewable by the user gripping the housing;
4	input devices operable by the user when the user grips the housing;
5	a connector for, in use, operatively connecting to portable storage media storing video
6	game programs for the video games;
7	first processing circuitry for processing video game programs having a first program
8	specification; and
9	second processing circuitry for processing video game programs having a second program
10	specification.
	2. The hand-held display system according to claim 1, wherein the first program
2	specification is an 8-bit specification and the second program specification is a 32-bit specification.
(*),§ (1 <u>),</u> §	The hand-held display system according to claim 1, wherein the input devices
2	comprise one or more first input devices arranged on one side of the liquid crystal display and one
3	or more second input devices arranged on the other side of the liquid crystal display, the first input
4	devices accessible using a thumb of one hand and the second input devices accessible using a
	thumb of the other hand.
71 (1)	than of the other hand.
5	4. The hand-held display system according to claim 3, wherein the input devices
2	further comprise shoulder buttons at the upper corners of the housing, the should buttons
3	accessible using the index fingers of the user's hands.
	·
1	5. The hand-held display system according to claim 1, wherein the memory space of a
2	portable memory medium storing a video game program in accordance with the second program
3	specification is mapped to two or more memory spaces of the second processing circuitry each
4	having different access speeds.
1	6. The hand-held display system according to claim 5, further comprising:
2	1 3 1
	a register for setting individual access speeds for each of the memory spaces of the
3	processing circuitry to which the memory space of the computer-readable medium is mapped.
	•

- 7. The hand-held display system according to claim 6, wherein the register sets an access speed in which a first access has 3 wait cycles and a second access has 1 wait cycle.
- 1 8. The hand-held display system according to claim 1, wherein the video game 2 program is stored in a ROM portion of the portable memory medium.

e da

- 1 9. The hand-held display system according to claim 1, wherein the portable memory 2 medium is accessible both randomly and sequentially.
  - The hand-held display system according to claim 9, further comprising:
    an address counter responsive to a memory read signal for counting up memory addresses
    to sequentially access the computer-readable medium.
    - 11. The hand-held display system according to claim 1, wherein the second processing circuitry renders objects on one or more background screens on the liquid crystal display screen, wherein the background screen is selectively rendered in one of a character format and a bit-map format.
    - 12. The hand-held display system according to claim 11, wherein the components of the background screen are characters of  $8 \times 8$  dots in the character format.
    - 13. The hand-held display system according to claim 11, wherein each of the one or more background screens has an associated display priority relative to the other background screens.
  - 14. The hand-held display system according to claim 11, wherein the objects are rendered in the character format.
- 1 15. The hand-held display system according to claim 11, wherein each of the objects 2 has an associated display priority relative to the other objects.
  - 16. The hand-held display system according to claim 1, wherein the first processing circuitry comprises an *n*-bit bus controller and the second processing circuitry comprises a multiplex bus controller and an *n*-bit bus controller.

17.	The hand-held display systen	n according to claim 16, wherein the <i>n</i> -bit bus
controller of	the first processing circuitry co	mprises an 8-bit bus controller for accessing portable
memory med	ia storing video game program	s having the first program specification, the multiplex
bus controlle	r of the second processing circ	uitry accesses first portions of portable memory media
storing video	game programs having the sec	cond program specification, and the n-bit bus controlled
of the second	processing circuitry comprise	s an 8-bit bus controller for accessing second portions
of portable m	nemory media storing video gar	me programs having the second program specification.
10	A hand hald display suction	

A hand-held display system for playing video games, comprising: a housing grippable by a user's hands; a liquid crystal display viewable by the user gripping the housing; input devices operable by the user when the user grips the housing; a connector for, in use, operatively connecting to portable storage media storing video 5 6 7 8

1

2

3

4

5

6

7

1

2

3

4

ŧΞ 1

3

1

2

game programs for the video games; and processing circuitry for processing video game programs, and

wherein the liquid crystal display has first and second display formats for displaying images generated by the processing circuitry.

- 19. The hand-held display system according to claim 18, wherein the first display format is a wide-screen display format and the second display format is a non-widescreen display format.
- The hand-held display system according to claim 18, wherein the input devices are 20. operable to selectively switch between the first and second display formats.

1	21. A hand-held display system for playing a video game, comprising:
2	a housing grippable by a user's hands;
3	a liquid crystal display viewable by the user gripping the housing;
4	input devices operable by the user when the user grips the housing;
5	a connector for, in use, operatively connecting to a computer-readable medium having
6	stored thereon a video game program for the video game;
7	a first boot ROM storing code that is executed if the computer-readable medium is
8	determined to store a video game program of a first specification, and
9	a second boot ROM storing code that is executed if the computer-readable medium is
10	determined to store a video game program of a second specification.
1	The hand-held display system according to-claim 21, wherein the first specification
2	is an 8-bit specification and the second specification is a 32-bit specification.
2	The hand-held display system according to claim 21, wherein the input devices
2	comprise one or more first input devices arranged on one side of the liquid crystal display and one
3	or more second input devices arranged on the other side of the liquid crystal display, the first input
4	devices accessible using a thumb of one hand and the second input devices accessible using a
5	thumb of the other hand.
1 2 3	The hand-held display system according to claim 23, wherein the input devices
2	further comprise shoulder buttons at the upper corners of the housing, the should buttons
3	accessible using the index fingers of the user's hands.
1	The hand-held display system according to claim 21, further comprising:
2	a first processing circuit for processing a video game program of the first specification; and
3	a second processing circuit for processing a video game program of the second

specification.

Ι .	A nand-neid display system for playing a video game, comprising:
2	a housing grippable by a user's hands;
3	a liquid crystal display viewable by the user gripping the housing;
4	input devices operable by the user when the user grips the housing;
5	a connector for, in use, operatively connecting to a computer-readable medium having
6	stored thereon a video game program for the video game;
7	processing circuitry for processing the video game program,
8	wherein the memory space of the computer-readable medium is mapped to two or more
9	memory spaces of the processing circuitry each having a different access speeds.
1	27. The hand-held display system according to claim 26, further comprising:
2	a register for setting individual access speeds for each of the memory spaces of the
31	processing circuitry to which the memory space of the computer-readable medium is mapped.
1	28. The hand-held display system according to claim 27, wherein the register sets an
3	access speed in which a first access has 3 wait cycles and a second access has 1 wait cycle.
la Ij	29. The hand-held display system according to claim 26, wherein the video program i
	stored in a ROM portion of the computer-readable medium.
	The hand-held display system according to claim 26, wherein the computer-
2. 11 21	readable medium is accessible both randomly and sequentially.
1	The hand-held display system according to claim 30, further comprising:
2	an address counter responsive to a memory read signal for counting up memory addresse
3	to sequentially access the computer-readable medium.

1	32. A hand-held display system for playing a video game, comprising:
2 .	a housing grippable by a user's hands;
3	a liquid crystal display viewable by the user gripping the housing;
4	input devices operable by the user when the user grips the housing;
5	a connector for, in use, operatively connecting to a computer-readable medium having
6	stored thereon a video game program for the video game;
7	processing circuitry for processing the video game program to render objects on one or
8	more background screens on the liquid crystal display screen,
9	wherein the background screen is selectively rendered in one of a character format and a
10	bit-map format.
1	The hand-held display system according to claim 32, wherein the components of
2	the background screen are characters of 8 x 8 dots in the character format.
1	34. The hand-held display system according to claim 32, wherein each of the one or
2	more background screens has an associated display priority relative to the other background
3.	screens.

35. The hand-held display system according to claim 32, wherein the objects are rendered in the character format.

display system, each of the master and slave hand-held display systems adapted for playing a game and comprising a housing grippable by a user's hands, a liquid crystal display viewable user gripping the housing, input devices operable by the user when the user grips the housin connector for, in use, operatively connecting to a computer-readable medium having stored thereon a video game program for the video game, processing circuitry for processing the v game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display system a second connector for connecting to the interface of the slave hand-held display system and a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprising.		
game and comprising a housing grippable by a user's hands, a liquid crystal display viewable user gripping the housing, input devices operable by the user when the user grips the housing connector for, in use, operatively connecting to a computer-readable medium having stored thereon a video game program for the video game, processing circuitry for processing the v game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display system as second connector for connecting to the interface of the slave hand-held display system and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprising communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	1	36. A cable for connecting a master hand-held display systems with a slave hand-held
user gripping the housing, input devices operable by the user when the user grips the housing connector for, in use, operatively connecting to a computer-readable medium having stored thereon a video game program for the video game, processing circuitry for processing the video game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display system as second connector for connecting to the interface of the slave hand-held display system and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprise communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	2	display system, each of the master and slave hand-held display systems adapted for playing a video
connector for, in use, operatively connecting to a computer-readable medium having stored thereon a video game program for the video game, processing circuitry for processing the v game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display system a second connector for connecting to the interface of the slave hand-held display system and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprising communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	3	game and comprising a housing grippable by a user's hands, a liquid crystal display viewable by the
thereon a video game program for the video game, processing circuitry for processing the video game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display system as second connector for connecting to the interface of the slave hand-held display system and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprising communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	4	user gripping the housing, input devices operable by the user when the user grips the housing, a
game program, and an interface for, in use, connecting to the cable, the cable comprising:  a first connector for connecting to the interface of the master hand-held display systems a second connector for connecting to the interface of the slave hand-held display systems and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the master hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the master hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the interface of the slave hand-held display systems further comprising:  a first connector for connecting to the slave hand-held display systems further comprising:  a first connector for connecting to the slave hand-held display systems further comprising to the slave hand-held display systems further comprising to the slave hand-held display systems further comprising to the slave hand-held display systems further capture hand-held display systems further capture hand-held	5	connector for, in use, operatively connecting to a computer-readable medium having stored
a first connector for connecting to the interface of the master hand-held display systems a second connector for connecting to the interface of the slave hand-held display systems and a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprise communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	6	thereon a video game program for the video game, processing circuitry for processing the video
a second connector for connecting to the interface of the slave hand-held display system and  a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further comprise communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	7	game program, and an interface for, in use, connecting to the cable, the cable comprising:
a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further compri  communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	8	a first connector for connecting to the interface of the master hand-held display system;
a third connector for connecting to a connector of another cable,  wherein each of the master and slave hand-held display systems further compri  communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	9	a second connector for connecting to the interface of the slave hand-held display system;
wherein each of the master and slave hand-held display systems further comprise communication circuitry for communicating data hand-held display systems connected to the third connector of the cable.	10	and
communication circuitry for communicating data therebetween and between any additional hand-held display systems connected to the third connector of the cable.	11	a third connector for connecting to a connector of another cable,
hand-held display systems connected to the third connector of the cable.  ADD WELLS OF THE CABLE		wherein each of the master and slave hand-held display systems further comprise
hand-held display systems connected to the third connector of the cable.  ADD WELLS OF THE CABLE	13	communication circuitry for communicating data therebetween and between any additional slave
	14	hand-held display systems connected to the third connector of the cable.
	:= :::  - ::::	4 212 5
	-	
	is dis	
12 M <sup>2</sup>		